

Customer No.: 31561
Application No: 10/709,925
Docket No.: 11238-US-PA

AMENDMENTS

To the Claims:

1. (currently amended) A multi-chip package module, comprising:

a first chip having an active surface;

a second chip positioned ~~over~~under the active surface of the first chip as a flip -chip structure, wherein a height of the second chip in a direction perpendicular to the active surface is defined as h1;

a plurality of first bumps positioned between the active surface of the first chip and the second chip, wherein a height of the first bumps in the direction perpendicular to the active surface is defined as h2;~~and~~

a plurality of contacts, protruding from the active surface of the first chip, wherein a height of the contacts in the direction perpendicular to the active surface is defined as h3, and values of h1, h2, and h3 are related by an inequality of $h3 \geq h1 + h2$; and

an underfill film made from an insulating material and formed over the active surface of the first chip, wherein each of the contacts comprises a plurality of stacked second bumps, and the underfill film covers the stacked second bumps of the contacts and exposes the top surface of the contacts.

2. (canceled)

3. (withdrawn) The multi-chip package module of claim 1, wherein each of the contacts comprises a cylindrical metallic rod.

Customer No.: 31561
Application No: 10/709,925
Docket No.: 11238-US-PA

4. (original) The multi-chip package module of claim 1, further comprising an insulating material over the active surface of the first chip that encloses the first bumps and the contacts.

5. (withdrawn) The multi-chip package module of claim 1, wherein a portion of the second chip extends over an area outside the active surface of the first chip.

6. (original) The multi-chip package module of claim 1, further comprising a third chip and a plurality of third bumps, wherein the third chip is positioned over the active surface of the first chip as a flip chip structure, the third bumps are positioned between the active surface of the first chip and the third chip, a height of the third chip in the direction perpendicular to the active surface being defined as h_4 , a height of the third bumps in the direction perpendicular to the active surface being defined as h_5 , and values of h_3 , h_4 and h_5 are related by an inequality of $h_3 \geq h_4 + h_5$.

7. (currently amended) A multi-chip package structure, comprising:

a substrate;

a plurality of contacts;

a first chip having an active surface that faces the substrate, wherein the contacts are positioned between the first chip and the substrate, and a distance between the substrate and the active surface in a direction perpendicular to the active surface is defined as d ;

a second chip positioned between the first chip and the substrate, wherein a height of the second chip in the direction perpendicular to the active surface is defined as h_1 ; ~~and~~

a plurality of first bumps positioned between the active surface of the first chip and the second chip for electric connection, wherein a height of the first bumps in the direction

Customer No.: 31561
Application No: 10/709,925
Docket No.: 11238-US-PA

perpendicular to the active surface is defined as h_2 and values of h_1 , h_2 and d are related by an inequality of $d \geq h_1 + h_2$; and

an underfill film made from an insulating material and formed over the active surface of the first chip, wherein each of the contacts comprises a plurality of stacked second bumps, and the underfill film covers the stacked second bumps of the contacts and exposes the top surface of the contacts.

8. (canceled)

9. (withdrawn) The multi-chip package structure of claim 7, wherein each of the contacts comprises a cylindrical metallic rod.

10. (original) The multi-chip package structure of claim 7, further comprising an insulating material over the active surface of the first chip that encloses the first bumps and the contacts.

11. (withdrawn) The multi-chip package structure of claim 7, wherein a portion of the second chip extends over an area outside the active surface of the first chip.

12. (original) The multi-chip package structure of claim 7, wherein a height of the contacts in the direction perpendicular to the active surface is defined as h_3 and values of h_1 , h_2 and h_3 are related by an inequality of $h_3 \geq h_1 + h_2$.

13. (original) The multi-chip package structure of claim 7, further comprising a third chip and a plurality of third bumps such that the third chip is positioned between the first chip and the substrate, as well as the third bumps are positioned between the first chip and the third chip to connect together as a flip chip structure, wherein a height of the third chip in the direction perpendicular to the active surface is defined as h_4 and a height of the third bumps

Customer No.: 31561
Application No: 10/709,925
Docket No.: 11238-US-PA

in the direction perpendicular to the active surface is defined as h_5 , and values of d , h_4 and h_5 are related by an inequality of $d \geq h_4 + h_5$.

14. (original) The multi-chip package structure of claim 13, wherein a height of the contacts in the direction perpendicular to the active surface is defined as h_3 and values of h_3 , h_4 and h_5 are related by an inequality of $h_3 \geq h_4 + h_5$.

15. (withdrawn) A multi-chip package structure, comprising:

a substrate;

a plurality of contacts;

a first chip having an active surface that faces the substrate, wherein the contacts are positioned between the first chip and the substrate to connect the first chip and the substrate as a flip chip structure, and a distance between the substrate and the active surface in the direction perpendicular to the active surface is defined as d ; and

at least a package module, set up between the first chip and the substrate, and connected to the first chip, wherein the package module comprises at least a chip and a height of the package module in the direction perpendicular to the active surface is defined as h_1 , and values of d and h_1 are related by an inequality of $d \geq h_1$.

16. (withdrawn) The multi-chip package structure of claim 15, wherein each of the contacts comprises a plurality of stacked bumps.

17. (withdrawn) The multi-chip package structure of claim 15, wherein each of the contacts comprises a cylindrical metallic rod.

18. (withdrawn) The multi-chip package structure of claim 15, wherein the package module is an electrically-testable package module.

Customer No.: 31561
Application No: 10/709,925
Docket No.: 11238-US-PA

19. (withdrawn) The multi-chip package structure of claim 15, wherein the package module comprises a multi-chip module (MCM).

20. (withdrawn) The multi-chip package structure of claim 15, wherein the package module comprises a system in a package (SIP).

21. (withdrawn) The multi-chip package structure of claim 15, wherein a portion of the package module extends over an area outside the active surface of the first chip.

22. (withdrawn) The multi-chip package structure of claim 15, wherein the package module comprises a chip scale package (CSP).

23. (withdrawn) The multi-chip package structure of claim 15, wherein a height of the contacts in the direction perpendicular to the active surface is defined as $h3$ and the values of $h1$ and $h3$ are related by an inequality of $h3 \geq h1$.